

# LM Non-Slip 100S

Medium Textured Grade

---

**PRODUCT  
DESCRIPTION**

Coarse particle size grades of micronised polypropylene are used for adding texture, structure, and non-slip properties to a wide variety of paints and coatings.

---

**INTENDED  
USES**

- Anti-Slip Additive for Topcoat

---

**FEATURES**

- Medium textured coating surface
- Excellent Durability
- Ideal for Non-Slip purposes
- Easy to disperse with high-speed mixing

---

**PRODUCT DATA**

<b>Finish</b>	Anti-Slip Finish
<b>Colour</b>	White
<b>Maximum Particle Size</b>	< 150 µm (20 mesh)
<b>Mean Particle Size</b>	80 - 100 µm
<b>Flash Point</b>	> 277 °C
<b>Melting Point</b>	160 - 170 °C
<b>Specific Gravity</b>	0.89 @ 25°C

---

**APPLICATION****Mixing**

Recommended Addition Levels: 3.0 - 10.0%

---

**COMPATIBILITY****Topcoats**

Aralox-FL170  
Opalon-F45  
Opalon-S30

---

**STORAGE &  
HANDLING**

Store in dry, shaded conditions away from sources of heat and in the original properly sealed containers. Protect from heat and frost. Protect contents from moisture.

---

**PACK SIZE**

1Kg Kits  
1Kg of LM Non-Slip 100S in a 2L Container

---

**DISCLAIMER**

The information contained herein is offered without charge and is for use by technically qualified personnel at their own risk. All statements, technical information and recommendations contained herein are based on tests and data which we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and no warranty of any kind is made with respect thereto.

---

LiquiMix Pty Ltd - ABN 32 062 887 585  
24 Rosa Place, Richlands QLD 4077  
Phone: 1300 123 085

Web: - [www.liquimix.com](http://www.liquimix.com)  
Sales Enquiries: - [sales@liquimix.com](mailto:sales@liquimix.com)  
Account Enquiries: - [accounts@liquimix.com](mailto:accounts@liquimix.com)